

# BENCO

---

## SALES INC

123 STOUT DRIVE, CROSSVILLE, TN 38555 • 931-484-9578

### **BENCO #B94 INDUSTRIAL PAINT REMOVER**

#### Description

Benco #B94 is a slightly viscous liquid, water-rinsable remover capable of stripping paints and finishes. #B94 will strip shellacs, varnishes, lacquers, polyurethanes, enamels, Acrylics, epoxies, conversion varnishes, and polyesters. #B94 has a long wet life and slow evaporation rate. #B94 is formulated with the highest quality solvents, surfactants, and additives.

#### Characteristics

Does not contain any Methylene Chloride, DMF, DBE, Methanol or HAP's.

Specific Gravity	1.03 (8.66 lbs. /gal.)
Percent Volatile	>95%
VOC Content	15 grams/liter
Vapor Pressure	.1 mm Hg
Boiling Point (Initial)	219 degrees F
Freezing Point	Less than 30 F
Flash Point:	>200 F
Shelf Life:	Minimum 1 year, unopened, stored at less than 75 F

#### Application

Apply Benco #B94 by brush, spray, flow on, or immersion.

For best results, use this product in polyethylene tanks. Steel tanks are also acceptable, but product will remove galvanizing from galvanized tanks.

Apply a liberal coat and allow product to strip all coatings prior to removal. Thin coatings and clear finishes will usually strip in less than 15 minutes.

For items with multiple coatings, apply and allow adequate time for the remover to penetrate to the substrate. In some applications, several hours may be required to penetrate multiple coatings. This product will remain wet and active for extended periods. An overnight application is appropriate for heavily painted items, conversion coatings, and polyester.

Removed finishes with stripper can be reapplied to extend the life of the stripper.

For best results, once finishes are removed from the surface, rinse with water or alcohol. Allow adequate time for the remover to completely evaporate from the surface prior to finishing.

Clean up with water.

Contact Benco at 800-632-3626 for technical assistance.