



P.O. Box 3649 • Crossville, TN 38557 • (931) 484-9578 • Fax: (931) 484-7614

BENCO #B95 INDUSTRIAL PAINT REMOVER

Description

Benco #B95 is a semi-paste, water-rinsable remover capable of stripping paints and finishes. #B95 will strip shellacs, varnishes, lacquers, polyurethanes, enamels, acrylics, epoxies, conversion varnishes, and polyesters. #B95 has a wet life exceeding 12 hours and will cling to vertical surfaces. #B95 is formulated with the highest quality solvents, surfactants, and additives.

Characteristics

Does not contain any Methylene Chloride, DMF, DBE, Methanol or HAP's.

Specific Gravity	1.01 (8.41 lbs./gal.)
Percent Volatile	>95%
VOC Content	0 grams/liter
Vapor Pressure	.1 mm Hg
Boiling Point (Initial)	219 degrees F
Freezing Point	Less than 30 F
Flash Point:	>200 F
Shelf Life:	Minimum 1 year, unopened, stored at less than 75 F

Application

Apply Benco #B95 by brush or roller, brushing in 1 direction only, or by spray.

Apply a liberal coat and allow product to strip all coatings prior to removal. Thin coatings and clear finishes will usually strip in less than 60 minutes.

For items with multiple coatings, apply a liberal coat of stripper, and allow adequate time for the remover to penetrate to the substrate. In some applications, several hours may be required to penetrate multiple coatings. This product will remain wet and active for extended periods. An overnight application is appropriate for heavily painted items, conversion coatings, and polyester.

Stripped finishes can be removed with a scraper. Removed finishes with stripper can be reapplied to extend the life of the stripper.

For best results, once finishes are removed from the surface, rinse with water or alcohol. Allow adequate time for the remover to completely evaporate from the surface prior to finishing.

Clean up with water.

Contact Benco at 800-632-3626 for technical assistance.