



123 STOUT DRIVE, CROSSVILLE, TN 38555 • 931-484-9578

BESWAY F14 INDUSTRIAL PAINT REMOVER

Description

Besway F14 is a liquid, non-flammable, neutral pH remover capable of stripping most paints and finishes. F14 will rapidly strip shellacs, varnishes, lacquers, polyurethanes, Enamels, latex, and acrylics. F14 will not darken wood surfaces from stripping, yet it will remove most stains. F14 is formulated with the highest quality virgin solvents, surfactants, and additives.

Characteristics

Methylene Chloride Content	75-80% by weight
Specific Gravity	1.19 (9.91 lbs./gal.)
Percent Volatile	>95%
VOC Content	111 grams/liter (0.925 lbs./gal.)
Boiling Point (Initial)	104 degrees F
Freezing Point	Less than -40 F
Flash Point:	N/A
Shelf Life:	Minimum 1 year, unopened, stored at less than 75 F

Application

Apply Besway F14 by immersion or flowing over surface. Product can be pumped with a Benco electric flow system or diaphragm flow system.

Apply a liberal coat and allow product to strip all coatings prior to removal. Thin coatings and clear finishes will usually strip in 2 -30 minutes.

For items with multiple coatings, apply repeated liberal coats of stripper until all finishes are removed. Avoid brushing until the base coat is loosened from the surface.

If the product has dried on the surface, reapply a coat of stripper prior to removal of finish for best results.

Stripped finishes can be removed with a brush or squeegee. In a flow system, allow stripped residue to settle in container, and decant stripper for reuse.

For best results, once finishes are removed from the surface, rinse with water or denatured alcohol.

Contact Benco at 800-632-3626 for technical assistance.