

Safety Data Sheet

Section 1, Identification

Product Identifier: F-14 Industrial Paint Remover
Synonyms: Liquid Paint Remover
CAS No.: Mixture
Manufacture Stock Number: F-14
Intended Use: Paint and Finish Remover

Manufacturer: BSI Companies
123 Stout Drive
Crossville, TN. 38555
931-484-9578

Emergency Phone: 1(800) 535-5053 INFOTRAC 24 hour response
Information Phone: (931) 484-9578
(931) 4847614

Section 2, Hazards Identification

Classification: GHS-US Classification

Signal Word: Warning

Pictogram:



Hazard Statement: H301 Toxic if swallowed
H315 Causes skin irritation.
H319 Causes eye irritation.
H335 Causes respiratory irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H373 May cause damage to organs (liver, blood) through repeated or prolonged exposure if swallowed.
H373 May cause damage to organs (Central nervous system) through repeated or prolonged exposure if inhaled.

Precautionary Statements: P201 Obtain Special instructions before use.
P202 Do not handle until all safety precaution have been read and understood.
P234 Keep only in original container.
P261 Avoid breathing fumes, gas, mist, vapors or spray.
P262 Do not get in eyes, on skin, or on clothing.
P263 Avoid contact during pregnancy or while nursing.

BSI Companies
Safety Data Sheet

P264 Wash thoroughly after handling.
P270 Do not eat/drink/smoke while using this product.
P271 Use only out doors or in well-ventilated area.
P281 Use personal protective equipment as required. (See section 8)
P284 Keep away from heat/sparks/open flame/hot surfaces - No Smoking.

Unknown Acute Toxicity: No additional information available.
Hazards not Otherwise Classified: No additional information available.

Section 3, Composition/Information on Ingredients

CAS No.	Ingredient Name	Weight Percentage
75-09-2	Methylene Chloride	70 - 80 %
67-56-1	Methanol	10 - 20 %
1310-58-3	Potassium Hydroxide	2 - 3 %

Occupational exposure limits, if available, are listed in section 8

Regulatory information listed in section 15

Section 4, First Aid Measures

Eye: Flush with large amounts of water for at least 15 minutes, lifting upper and lower lids occasionally. Get medical attention.

Ingestion: Call physician, poison control center, or hospital emergency room IMMEDIATELY.

NEVER GIVE ANYTHING TO AN UNCONCIOUS PERSON.

Skin: Thoroughly wash exposed areas with soap and water. Remove contaminated clothing.

Launder contaminated clothing before re-use.

Inhalation: Move affected individual to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm, quiet, and get medical attention.

Section 5, Fire Fighting Measures

Suitable Extinguishing Media: Use water spray, alcohol resistant foam, dry chemical or carbon dioxide.

Unsuitable Extinguishing Media: Do not use a heavy water stream. This may spread burning liquid.

Fire Fighting Instructions: Exercise caution when fighting any chemical fire. Use self contained breathing apparatus and protective clothing. Use water spray to keep fire exposed containers cool.

Unusual Fire and explosion hazards: This product contains chlorinated solvents, which can form flammable vapor/air mixtures at elevated temperatures (above ambient) . At high temperatures (during fire) the product decomposes, creating Hydrochloric acid gas and Carbon Monoxide.

Section 6, Accidental Release Measures

Emergency Procedures: Stop spillage/leakage at the source if safe to do so. Remove sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation of affected area.

Personal Protective Equipment: Use required personal protective equipment. See section 8.

General Measures: Cover spilled product with an inert absorbent i.e. Vermiculite or similar material.

Place wet absorbent into metal container and secure with lid. Label container with appropriate information. **Do not use saw dust.**

Environmental Precautions: Prevent further leakage or spillage if safe to do so. Do not allow product to enter drains.

Reference to other sections: Section 8, Exposure Controls and Personal Protection.

Section 7, Handling and Storage

Handling: Avoid contact with skin or eyes. See section 2. Avoid inhalation of vapors or mists.

Storage: Keep container tightly closed and store in a dry well ventilated area. Do not store in direct sunlight. Open slowly, product can develop unsafe pressure if stored in direct sunlight or above 80 F.

Section 8, Exposure Controls and Personal Protection

BSI Companies
Safety Data Sheet

Occupational Exposure Limits:

Ingredient	USA- ACGIH TLV	USA- OSHA TLV
Methylene Chloride	50 ppm TWA	125 ppm STEL, 25 ppm TWA
Methanol	250 ppm STEL	200 ppm TWA
Potassium Hydroxide	2 (mg/m ³) Ceiling	2 (mg/m ³) Ceiling

Appropriate Engineering Controls: Provide exhaust ventilation or other engineering controls to keep airborne concentrations below their respective threshold limit value. Ensure that eyewash and safety shower stations proximal to the work area location.

Personal Protective Equipment: Splash goggles/face shield, chemical resistant gloves, chemical resistant apron and proper foot protection i.e. steel toe boots. A self contained breathing apparatus should be used when vapor concentrations are above permitted exposure limits.

Other Protective Information: Personal Protective Equipment in case of spill or leakage: Self contained (full faced) breathing apparatus (SCBA), chemical resistant gloves, chemical resistant boots and protective clothing, full body Tyvek suit.

Use only with adequate ventilation. Local exhaust ventilation is necessary for most applications.

Lethal concentrations (Methylene Chloride) may exist in areas with poor ventilation. Contact Besway Systems, Inc. (615) 865-8310 for further information regarding vapor concentrations in your work areas. Methylene Chloride monitoring badges are available and may be necessary to determine if your processes are below permitted exposure limits for Methylene Chloride.

Section 9, Physical and Chemical Properties

Physical State: Liquid

Appearance: Clear colorless liquid.

Color: Colorless

Odor: Sweet ether like odor

pH: 9 – 10

Boiling Point: 104 F (Initial)

Vapor Density: >1 (Air = 1)

Vapor pressure: < 300 mm Hg @ 20 C

Specific Gravity: 1.160 - 1.190

Percent Volatile: > 97 %

Flash Point: None to boiling point.

Auto ignition Temperature: Not determined.

Section 10, Stability and Reactivity

Reactivity: None

Chemical Stability: Stable under normal conditions.

Hazardous Polymerization: Will not occur.

Conditions to Avoid: Contact with pure oxygen, alkali metals, open flames, electrical sparks and welding torches.

Incompatible Materials: Avoid contact with strong alkalies and strong oxidizing agents.

Hazardous Decomposition Products: None

Section 11, Toxicological Information

Acute Toxicity: LD50 Oral (rat) > 2,000 mg/kg

LC50 Inhalation (rat) 52,000 mg/m³

LD50 Dermal (rat) 2,000 mg/kg (OECD Test Guideline 402)

Skin corrosion/ irritation: Skin (rabbit). Result: Irritating to skin. (24 h)

Reproductive Toxicity: No data available

Symptoms/Injuries after Inhalation: Drowsiness or dizziness.

Symptoms/Injuries after Eye Contact: Sever pain and stinging to the eyes.

Symptoms/Injuries after Ingestion: May cause damage to organs, liver and blood if ingested.

BSI Companies
Safety Data Sheet

Other Information: Toxicological information determined using bridging principals from current raw material SDS information. IARC: 2B- Group 2B: Possibly carcinogenic to humans (Methylene Chloride).

Section 12, Ecological Information

Keep Out of Water Ways. Contain all spills and keep away from drains.

Toxicity to Fish Methylene Chloride: LC50 (fathead minnow) – 193 mg/l (96 hr.)

Persistence and degradability: No data available.

Bio accumulative potential: No data available.

Mobility in soil: No data available.

Section 13, Disposal

Dispose of in accordance with local, regional, national and international regulations.

Section 14, Transportation Information

UN Number: UN 3066

UN Number (DOT): UN 3066

Proper Shipping Name: UN3066, Paint Related material, 8, PGII

DOT Classification: 8

Hazard Classification: Corrosive

Hazard label: Corrosive

Packing Group: Group II

Section 15, Regulatory Information

Materials Listed on the United States TSCA (Toxic Substance Control Act) Inventory.

California Prop 65. This product contains a chemical known to the State of California to cause cancer (Methylene Chloride). OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR1910.1200).

Section 16, Other Information

Revision Date: June 20, 2016

Other Information: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

Special Precautions to be Taken in Handling & Storage: Exercise reasonable care and caution. Avoid breathing vapors. Store in a cool place out of direct sunlight. Concentrated vapors of this product are heavier than air and will collect in low areas such as pits and degreasers, storage tanks, and other confined areas. Do not enter those areas where vapors of this product are suspected unless special breathing apparatus is used and an observer is present for assistance. Not intended for use on bathtubs, bathrooms, or enclosed areas.

Do not pressure product out of container with air. When opening bung, open bung partially and vent any accumulated pressure before removing bung completely. Empty product containers may contain liquid or vapor residues of this product. All precautions suggested in this Data Sheet apply to empty containers also. Empty containers are property of Benco Sales, Inc. and should not be sold to individuals or other parties. Do not repackage this product for resale. Any product purchased for resale must have this SDS attached to each container and must be in original container. If each container does not have and SDS, call Benco at 800-632-3626.

Do not remove or deface labels off containers.

This information is based on our knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not be construed as guaranteeing any specific property of the product.